



Armada Uplight Wall Lantern Installation Guide

Product codes: 09184, 09185, 09186

INSTRUCTIONS FOR USE AND INSTALLATION GENERAL INFORMATION & TECHNICAL SPECIFICATIONS

PRODUCTS MANUFACTURED IN EU

- 230V ~ 50Hz
- Class I
- E27 porcelain lamp holder
- Not intended for mesh connection.
- Internal lamp connection to fixed wiring.
- 3G1.5 power cable should be used for the connection of the light fixture.
- Only one bulb is needed.

GENERAL INFORMATION ABOUT SAFETY

- Before any work, turn off the main supplies.
- Installation should only be carried out by a qualified electrician, who should be aware of the current Regulations on Internal & External Installations.
- In case of glass breakage, replace immediately.
- Lightbulb Wattage should never exceed the Wattage (W) indicated on the label or the packaging of the light fixture.
- The light fixture must be connected to a line protected by a differential circuit breaker, while the nominal persistent operating current should not exceed 30mA (leakage relay).

Included in the package:

- 1 Light fixture

LIGHT FIXTURE INSTALLATION



A. FIXING THE LIGHT FIXTURE ON A MOUNTING SURFACE

- Unscrew the cage and remove it from the body of the light fixture.
- Using the body of the light fixture as a template, mark the surface where the fixture will be mounted.
- Drill holes on the mounting surface.
- Insert wall plugs into the drilled holes.
- Pass the cable through the body of the light fixture.
- Using the supplied wall-plugs and screws, fix the body to the mounting surface.

B. CONNECTING THE POWER CABLE

- Connect the line (brown) and neutral (blue) wires to the lamp holder and the grounding wire (yellow/green) to the body of the light fixture using the supplied terminal **1**, using the supplied screw and M4 washer.
- Screw the lamp holder back in place.
- Fix the lamp holder in the cage.
- Screw the cage and fasten the cage to the body of the light fixture.
- Switch on the power supply.

C. REPLACING THE LIGHTBULB

- Turn off the mains supply.
- Unscrew the cage from the light fixture unless it has completely cooled down as it may cause burns.
- Remove the burnt-out bulb.
- Insert the new bulb(s) to the correct wattage.
- Avoid touching the bulb(s) with bare hands.
- Do not use a bulb with a higher wattage than is indicated.
- Screw the cage back to the light fixture gently.
- Ensure the cage is properly fastened and firmly holding the bulb(s) in the lamp holder.
- When replacing the bulb, do not touch the bulb with bare hands as it may cause damage to the bulb and reduce its lifespan. Use gloves for replacing the bulb.

The manufacturer bears no responsibility for any injury or damage resulting from incorrect installation of the product.